

Specifications



Photo is representative



Eaton FRS-R-15

Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 15 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series FRS-R fuse
CATALOG NUMBER	FRS-R-15
UPC	051712508308
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.165 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked

Electrical rating	
AMPERAGE RATING	15 A
INTERRUPT RATING	200 kAIC at 600 Vac 20 kAIC at 300 Vdc
RESPONSE TIME	10 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

General information	
CLASS	Class RK5
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating

Physical details	
NUMBER OF ELEMENTS	Dual
PACKAGING TYPE	Standard

Resources	
CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL SERVICE BULLETINS	Bussmann series FRS-R 600 V Class R up to 60 A fuse data sheet no. 1017

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE: